

# SAFETY DATA SHEET

Universal Hammer Finish

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : Universal Hammer Finish  
**Product description** : Aerosol. Paint.  
**Product type** : Aerosol.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Industrial uses: Uses of substances as such or in preparations* at industrial sites Consumer uses: Private households (= general public = consumers) Professional uses: Public domain (administration, education, entertainment, services, craftsmen)	
Uses advised against	Reason
None identified.	-

### 1.3 Details of the supplier of the safety data sheet

Rust-Oleum Corporation  
Portobello Industrial Estate  
Birtley  
County Durham  
United Kingdom  
DH3 2RE  
Telephone no.: +44 (0) 191 4106611  
Fax no.: +44 (0) 191 4920125

**e-mail address of person responsible for this SDS** : rpmeurohas@ro-m.com

### 1.4 Emergency telephone number

**Telephone number** : +44 (0) 207 858 1228  
**Hours of operation** : 24 / 7

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture  
**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**  
Flam. Aerosol 1, H222  
Eye Irrit. 2, H319  
STOT SE 3, H336

### Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

**Classification** : F+; R12  
Xi; R36  
R66, R67  
**Physical/chemical hazards** : Extremely flammable.

## SECTION 2: Hazards identification

**Human health hazards** : Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Danger

**Hazard statements** : Extremely flammable aerosol.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

### Precautionary statements

**General** : Read label before use. If medical advice is needed: Have product container or label at hand.

**Prevention** : Do not spray on an open flame or other ignition source. Avoid breathing vapour or spray. Wear protective gloves and eye protection: gloves: neoprene , safety glasses with side-shields.

**Response** : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

**Storage** : Store locked up.

**Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Supplemental label elements** : Pressurized container: may burst if heated. Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Keep out of reach of children.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

### Special packaging requirements

**Containers to be fitted with child-resistant fastenings** : Not applicable.

**Tactile warning of danger** : Not applicable.

### 2.3 Other hazards

**Other hazards which do not result in classification** : None known.

### SECTION 3: Composition/information on ingredients

Substance/mixture : Mixture

Product/ingredient name	Identifiers	%	Classification		Type
			67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	
acetone	REACH #: 01-2119471330-49 EC: 200-662-2 CAS: 67-64-1 Index: 606-001-00-8	35 - <50	F; R11 Xi; R36 R66, R67	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1] [2]
liquefied petroleum gas	EC: 270-704-2 CAS: 68476-85-7 Index: 649-202-00-6	15 - <20	F+; R12	Flam. Gas 1, H220	[2]
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	REACH #: 01-2119463258-33 EC: 919-857-5 Index: 649-327-00-6	<10	R10 Xn; R65 R66, R67	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304	[1] [2]
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	<15	R10 R66, R67	Flam. Liq. 3, H226 STOT SE 3, H336	[1] [2]
xylene (mixture of isomeres)	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	1 - <5	R10 Xn; R20/21 Xi; R38	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315	[1] [2]
2-methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6 Index: 607-195-00-7	1 - <5	R10	Flam. Liq. 3, H226	[2]
hydrocarbons, aromatic, C9	REACH #: 01-2119455851-35 EC: 918-668-5 Index: 649-356-00-4	1 - <2.5	R10 Xn; R65 Xi; R37 R66, R67 N; R51/53	Flam. Liq. 3, H226 STOT SE 3, H335 and H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	[1]
			<b>See Section 16 for the full text of the R-phrases declared above.</b>	<b>See Section 16 for the full text of the H statements declared above.</b>	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### 5.3 Advice for firefighters

## SECTION 5: Firefighting measures

- Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.
- Additional information** : Pressurized container: may burst if heated. Bursting aerosol containers may be propelled from a fire at high speed. Do not puncture, incinerate or store the container at temperatures above 49°C (120°F) or in direct sunlight.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also Section 8 for additional information on hygiene measures.

### 6.2 Environmental precautions

- : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

### 6.3 Methods and materials for containment and cleaning up

- : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Do not allow to enter drains or watercourses. Preferably clean with a detergent. Avoid using solvents. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- : Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.  
Operators should wear antistatic footwear and clothing and floors should be of the conducting type.  
Keep away from heat, sparks and flame. No sparking tools should be used.  
Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.  
Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.  
Put on appropriate personal protective equipment (see Section 8).

Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.

#### Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent

**SECTION 7: Handling and storage**

vapour concentration has fallen below the exposure limits.

**7.2 Conditions for safe storage, including any incompatibilities**

: Store in accordance with local regulations.

**Notes on joint storage**

Keep away from: oxidising agents, strong alkalis, strong acids.

**Additional information on storage conditions**

Observe label precautions. Do not store above the following temperature: 35°C (95°F). Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

**7.3 Specific end use(s)**

**Recommendations**

: Not available.

**Industrial sector specific solutions**

: Not available.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Occupational exposure limits**

Product/ingredient name	Exposure limit values
acetone	<b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b> STEL: 3620 mg/m <sup>3</sup> 15 minutes. STEL: 1500 ppm 15 minutes. TWA: 500 ppm 8 hours. TWA: 1210 mg/m <sup>3</sup> 8 hours.
liquefied petroleum gas	<b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b> STEL: 2180 mg/m <sup>3</sup> 15 minutes. STEL: 1250 ppm 15 minutes. TWA: 1750 mg/m <sup>3</sup> 8 hours. TWA: 1000 ppm 8 hours.
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	<b>EH40/2005 WELs (United Kingdom (UK), 8/2007).</b> STEL: 850 mg/m <sup>3</sup> , (as turpentine) 15 minutes. Form: Vapour TWA: 566 mg/m <sup>3</sup> , (as turpentine (100 ppm)) 8 hours. Form: Vapour
n-butyl acetate	<b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b> STEL: 966 mg/m <sup>3</sup> 15 minutes. STEL: 200 ppm 15 minutes. TWA: 724 mg/m <sup>3</sup> 8 hours. TWA: 150 ppm 8 hours.
xylene (mixture of isomeres)	<b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b> STEL: 441 mg/m <sup>3</sup> 15 minutes. STEL: 100 ppm 15 minutes. TWA: 220 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours.
2-methoxy-1-methylethyl acetate	<b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b> STEL: 548 mg/m <sup>3</sup> 15 minutes. STEL: 100 ppm 15 minutes. TWA: 274 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours.

## SECTION 8: Exposure controls/personal protection

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects	
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	DNEL	Long term Dermal	208 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	871 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Long term Oral, Dermal	125 mg/kg bw/day	Consumers	Systemic	
	DNEL	Long term Inhalation	185 mg/m <sup>3</sup>	Consumers	Systemic	
	n-butyl acetate	DNEL	Long term Dermal	7 mg/kg bw/day	Workers	Systemic
		DNEL	Long term Oral, Dermal	3.4 mg/kg bw/day	Consumers	Systemic
		DNEL	Short term Inhalation	960 mg/m <sup>3</sup>	Workers	Systemic
		DNEL	Short term Inhalation	960 mg/m <sup>3</sup>	Workers	Local
		DNEL	Long term Inhalation	480 mg/m <sup>3</sup>	Workers	Systemic
		DNEL	Long term Inhalation	480 mg/m <sup>3</sup>	Workers	Local
		DNEL	Short term Inhalation	859.7 mg/ m <sup>3</sup>	Consumers	Systemic
		DNEL	Short term Inhalation	859.7 mg/ m <sup>3</sup>	Consumers	Local
		DNEL	Long term Inhalation	102.34 mg/ m <sup>3</sup>	Consumers	Systemic
		DNEL	Long term Inhalation	102.34 mg/ m <sup>3</sup>	Consumers	Local
2-methoxy-1-methylethyl acetate	DNEL	Long term Inhalation	275 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Long term Dermal	153.5 mg/ m <sup>3</sup>	Workers	Systemic	
	DNEL	Long term Dermal	54.8 mg/m <sup>3</sup>	Consumers	Systemic	
	DNEL	Long term Oral	1.67 mg/m <sup>3</sup>	Consumers	Systemic	

### PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
n-butyl acetate	Fresh water	0.18 mg/l	-
	Marine	0.018 mg/l	-
	Fresh water sediment	0.981 mg/kg	-
	Marine water sediment	0.0981 mg/kg	-
	Soil	0.0903 mg/kg	-
	Sewage Treatment Plant	35.6 mg/l	-
	2-methoxy-1-methylethyl acetate	Fresh water	0.635 mg/l
Fresh water sediment		3.29 mg/kg	-



**SECTION 8: Exposure controls/personal protection**

	Marine water sediment	0.329 mg/kg	-
	Soil	0.29 mg/kg	-
	Sewage Treatment Plant	100 mg/l	-

**8.2 Exposure controls**

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

**Individual protection measures**

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety glasses with side shields. (EN166)

**Skin protection**

**Hand protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Gloves** : For prolonged or repeated handling, use the following type of gloves:

Recommended: > 8 hours (breakthrough time): neoprene.

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

EN 374-3 : 2003

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Body protection** : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres. (EN 1149-1)

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: organic vapour (Type A) and particulate filter. (EN 140)



## SECTION 8: Exposure controls/personal protection

**Environmental exposure controls** : Do not allow to enter drains or watercourses.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Liquid. [Aerosol.]

**Colour** : Various

**Odour** : Solvent-like [Slight]

**pH** : Not available.

**Melting point/freezing point** : Not available.

**Initial boiling point and boiling range** : Not available.

**Flash point** : Closed cup: -70°C

**Evaporation rate** : Not available.

**Flammability (solid, gas)** : Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.  
Slightly flammable in the presence of the following materials or conditions: shocks and mechanical impacts.  
In use, may form flammable/explosive vapour-air mixture. Vapour may travel a considerable distance to source of ignition and flash back.

**Burning time** : Not applicable.

**Burning rate** : Not applicable.

**Upper/lower flammability or explosive limits** : Not available.

**Vapour pressure** : 400 kPa [room temperature]

**Vapour density** : Not available.

**Relative density** : 0.76 to 0.78

**Solubility(ies)** : Not available.

**Solubility in water** : Not available.

**Partition coefficient: n-octanol/ water** : Not available.

**Auto-ignition temperature** : Not available.

**Decomposition temperature** : Not available.

**Viscosity** : Not available.

**Explosive properties** : Highly explosive in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts.  
Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not puncture, incinerate or store the container at temperatures above 49°C (120°F) or in direct sunlight. Container explosion may occur under fire conditions or when heated.  
Bursting aerosol containers may be propelled from a fire at high speed.

**Oxidising properties** : Not available.

### 9.2 Other information

#### Aerosol product

**Type of aerosol** : Spray

**Heat of combustion** : -13.09 kJ/g

No additional information.

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced. If involved in a fire, toxic gases including CO, CO<sub>2</sub> and smoke can be generated.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

There are no data available on the mixture itself. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
acetone	LD50 Oral	Rat	5800 mg/kg	-
n-butyl acetate	LC50 Inhalation Vapour	Rat	>21 mg/l	4 hours
	LC50 Inhalation Vapour	Rat	9700 mg/m <sup>3</sup>	4 hours
xylene (mixture of isomeres)	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Oral	Rat	14000 mg/kg	-
	LC50 Inhalation Gas.	Rat	5000 ppm	4 hours
	LC50 Inhalation Gas.	Rat	6670 ppm	4 hours
	LD50 Oral	Rat	4300 mg/kg	-
2-methoxy-1-methylethyl acetate	TDLo Dermal	Rabbit	4300 mg/kg	-
	LC50 Inhalation Vapour	Rat	4345 mg/l	6 hours
hydrocarbons, aromatic, C9	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	8532 mg/kg	-
	LD50 Oral	Mouse	8400 mg/kg	-
	LD50 Oral	Rat	8400 mg/kg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Acute toxicity estimates

Not available.

### Irritation/Corrosion

## SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
acetone	Eyes - Mild irritant	Human	-	186300 parts per million	-
	Eyes - Mild irritant	Rabbit	-	10 microliters	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Eyes - Severe irritant	Rabbit	-	20 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
n-butyl acetate	Skin - Mild irritant	Rabbit	-	395 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	100 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
xylene (mixture of isomeres)	Skin - Primary dermal irritation index (PDII)	Rabbit	0	-	-
	Eyes - Cornea opacity	Rabbit	1	-	-
	Eyes - Mild irritant	Rabbit	-	87 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams	-
	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	100 Percent	-
hydrocarbons, aromatic, C9	Eyes - Mild irritant	Rabbit	-	24 hours 100 microliters	-

### Conclusion/Summary

- Skin** : Based on available data, the classification criteria are not met.  
**Eyes** : Causes serious eye irritation.  
**Respiratory** : May cause drowsiness or dizziness.

### Sensitisation

Product/ingredient name	Route of exposure	Species	Result
hydrocarbons, C9-C11, n-/iso-/ cyclo-alkanes, < 2% aromatics	skin	Rabbit	Not sensitizing

### Conclusion/Summary

- Skin** : Based on available data, the classification criteria are not met.  
**Respiratory** : Based on available data, the classification criteria are not met.

### Mutagenicity

Product/ingredient name	Test	Experiment	Result
hydrocarbons, aromatic, C9	OECD 471	Subject: Bacteria	Negative

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Carcinogenicity

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
hydrocarbons, aromatic, C9	-	-	Negative	Mammal - species unspecified	Unreported	-

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

## SECTION 11: Toxicological information

### Teratogenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

**Other information** : Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

Product/ingredient name	Result	Species	Exposure
acetone	Acute LC50 8.64 to 8098 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 10 mg/l Fresh water	Daphnia spec. - Daphnia magna	48 hours
	Acute LC50 100 mg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 7.88 to 7280 mg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 4.95 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.1 ml/L Fresh water	Daphnia spec. - Daphnia magna - Neonate	21 days
hydrocarbons, C9-C11, n-/iso-/ cyclo-alkanes, < 2% aromatics	Acute NOEC 100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Chronic NOEC 0.23 mg/l	Daphnia spec.	-
n-butyl acetate	Chronic NOEC 0.131 mg/l	Fish	-
	Acute EC10 956 mg/l	Bacteria - Pseudomonas putida	18 hours
	Acute EC50 648 mg/l	Algae - Desmodesmus subspicatus	72 hours
	Acute LC50 32 mg/l Marine water	Crustaceans - Artemia salina - Nauplii	48 hours
2-methoxy-1-methylethyl acetate	Acute LC50 18 mg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 62 mg/l	Fish - Danio rerio	96 hours
	Acute EC50 408 to 500 mg/l	Daphnia spec.	48 hours
	Acute LC50 161 mg/l	Fish	96 hours
	Acute LC50 100 to 180 mg/l	Fish	96 hours

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
hydrocarbons, C9-C11, n-/iso-/ cyclo-alkanes, < 2% aromatics	OECD 301B	>80 % - Readily - 28 days	-	-
	OECD 301F	>80 % - Readily - 28 days	-	-
n-butyl acetate	-	90 % - Readily - 28 days	-	-
xylene (mixture of isomeres)	-	90 % - Readily - 5 days	-	-

## SECTION 12: Ecological information

**Conclusion/Summary** : This product has not been tested for biodegradation. Based on available data, the classification criteria are not met.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
acetone	-	-	Readily
hydrocarbons, C9-C11, n-/iso-/ cyclo-alkanes, < 2% aromatics	-	100%; < 28 day(s)	Readily
n-butyl acetate	-	-	Readily
xylene (mixture of isomeres)	-	-	Readily
2-methoxy-1-methylethyl acetate	-	-	Readily
hydrocarbons, aromatic, C9	-	-	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
acetone	-0.27 to 0.58	-	low
hydrocarbons, C9-C11, n-/iso-/ cyclo-alkanes, < 2% aromatics	5 to 6.5	-	high
n-butyl acetate	2.3	10	low
xylene (mixture of isomeres)	3.16	-	high
2-methoxy-1-methylethyl acetate	0.43	-	low
hydrocarbons, aromatic, C9	3.7 to 4.5	-	high

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Volatile. This product is likely to volatilise rapidly into the air because of its high vapour pressure.

### 12.5 Results of PBT and vPvB assessment

**PBT** : Not applicable.

**vPvB** : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

**Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

#### European waste catalogue (EWC)

### SECTION 13: Disposal considerations

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
20 01 27*	paint, inks, adhesives and resins containing dangerous substances


**Packaging**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Not emptied containers are hazardous waste.

**Special precautions** : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

### SECTION 14: Transport information

	ADR/RID	IMDG	IATA
<b>14.1 UN number</b>	UN 1950	UN 1950	UN 1950
<b>14.2 UN proper shipping name</b>	AEROSOLS Flammable [Limited quantity]	AEROSOLS Flammable [Limited quantity]	AEROSOLS, Flammable
<b>14.3 Transport hazard class(es)</b>	2	2.1	2.1 
<b>14.4 Packing group</b>	-	-	-
<b>14.5 Environmental hazards</b>	No.	No.	No.
<b>Additional information</b>	<p><b>Limited quantity:</b> LQ2</p> <p><b>Remarks:</b> ( &lt; 1L: ) Limited Quantity - ADR/IMDG 3.4</p> <p>ADR Tunnel code: (D)</p>	<p><b>Emergency schedules (EmS):</b> F-D + S-U</p> <p><b>Remarks:</b> Limited Quantity - ADR/IMDG 3.4</p>	<p><b>Passenger and Cargo Aircraft</b> Quantity limitation: 75 kg Packaging instructions: 203</p> <p><b>Cargo Aircraft Only</b> Quantity limitation: 150 kg Packaging instructions: 203</p> <p><b>Limited Quantities - Passenger Aircraft</b> Quantity limitation: 30 kg Packaging instructions: Y 203</p>

**14.6 Special precautions for user** : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.



## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

**CN code** : 3208 90 91

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### Other EU regulations

**VOC for Ready-for-Use Mixture** : Not applicable.

**Europe inventory** : Not determined.

**Priority List Chemicals (793/93/EEC)** : Listed

**Integrated pollution prevention and control list (IPPC) - Air** : Listed

**Aerosol dispensers** :

# 3

Extremely flammable

#### National regulations

**15.2 Chemical Safety Assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

🔍 Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** :

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- vPvB = Very Persistent and Very Bioaccumulative

**Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

## SECTION 16: Other information

Classification	Justification
Flam. Aerosol 1, H222 Eye Irrit. 2, H319 STOT SE 3, H336	Expert judgment Expert judgment Expert judgment

<b>Full text of abbreviated H statements</b>	: H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. May cause drowsiness or dizziness. and H336 H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
<b>Full text of classifications [CLP/GHS]</b>	: Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4 Aquatic Chronic 2, H411 AQUATIC TOXICITY (CHRONIC) - Category 2 Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Aerosol 1, H222 FLAMMABLE AEROSOLS - Category 1 Flam. Gas 1, H220 FLAMMABLE GASES - Category 1 Flam. Liq. 2, H225 FLAMMABLE LIQUIDS - Category 2 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2 STOT SE 3, H335 and H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation and Narcotic effects] - Category 3  STOT SE 3, H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Narcotic effects] - Category 3
<b>Full text of abbreviated R phrases</b>	: R12- Extremely flammable. R11- Highly flammable. R10- Flammable. R20/21- Harmful by inhalation and in contact with skin. R65- Harmful: may cause lung damage if swallowed. R36- Irritating to eyes. R37- Irritating to respiratory system. R38- Irritating to skin. R66- Repeated exposure may cause skin dryness or cracking. R67- Vapours may cause drowsiness and dizziness. R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
<b>Full text of classifications [DSD/DPD]</b>	: F+ - Extremely flammable F - Highly flammable Xn - Harmful Xi - Irritant N - Dangerous for the environment
<b>Date of printing</b>	: 25-03-2015.
<b>Date of issue/ Date of revision</b>	: 20-11-2014.
<b>Date of previous issue</b>	: 20-11-2014.
<b>Version</b>	: 1
<b>Notice to reader</b>	

## SECTION 16: Other information

***The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.***